

**Section** \_\_\_\_\_

HV Accessories

**Application** \_\_\_\_\_

Field

Laboratory



**PRODUCT BENEFITS**

Clean and precise stop making

**TOOL CAPACITY**

**Diameter** 35 - 90 mm  
1,378 - 3,543 inch

**Material** Aluminum with plastic inserts

**Rolling area** No

**TOOL DIMENSIONS**

**Length** 370 mm

**Width** 135 mm

**Height** 40 mm

**Weight without box** 1,2 Kg

**Packaging** None

## Multifunctional tool stop

**TO DO WHAT**

The BMF2 stop is fixed on the cable to stop the tools

It is used :

- On the outer sheath of the cable to stop the DMSR/40-90 tool
- On the semi-conductor to stop the CASR/35-75, LHS3 and LHM3R tools
- On the insulator to stop the LH3 tools



**Associated tool**

DMSR/40-90 - Reinforced stripping tool for hard outer sheath (PE, PEHD, Lead)

CASR/35-75 - Monofunction tool for bonded semiconductor, rounding up the cable

LHS3 - Monofunction tool for semiconductor

LHM3R - Monofunction tool for peelable semiconductor

LH3 - Monofunction tool for insulation

**ALROC SAS**

Z.I. de la Fonderie - 72160 TUFFE  
FRANCE

Phone: +33 2 43 71 11 80

Fax number : +33 2 43 71 16 51

www.alroc.fr

HV cables Tools

# BMF2



| Part Number | Diameter                       | Tool capacity                 |              | Dimensions          |                    |                   | Packaging |
|-------------|--------------------------------|-------------------------------|--------------|---------------------|--------------------|-------------------|-----------|
|             |                                | Material                      | Rolling area | Length              | Width              | Height            |           |
| <b>BMF2</b> | 35 - 90 mm<br>1,378 - 3,543 in | Aluminum with plastic inserts | No           | 370 mm<br>14,567 in | 135 mm<br>5,315 in | 40 mm<br>1,575 in | none      |