

# MV cables Tools

## MF1+/60



### Certifications

Approved by ENEDIS

### Section

MV Semi-conductor

### Application

Field  
Laboratory



### PRODUCT BENEFITS

Smooth finishing over insulation  
Sliding thrust embeded in the tools  
to set semiconductor remaining  
length  
Fine tuning of blade with a 'click' for  
each 1/10 mm

### TOOL CAPACITY

Diameter	18 - 60 mm 0,709 - 2,362 inch
Thickness capacity	0,4-1,4 mm / 0,016-0,055 in
Angle of the chamfer on the semiconductor	14,5°
Remaining length of the semiconductor	30-40-45-50-55 mm / 1,181- 1,575- 1,772- 1,969- 2,165 in

### TOOL DIMENSIONS

Length	305 mm
Width	85 mm
Height	100 mm
Weight without box	1,04 Kg
Packaging	Box

### ALROC SAS

Z.I. de la Fonderie - 72160 TUFFE  
FRANCE  
Phone: +33 2 43 71 11 80  
Fax number : +33 2 43 71 16 51  
www.alroc.fr

## Multifunction tool for bonded semiconductor

### TO DO WHAT

The MF1+/60 is a multifunction tool that enables the user to shave the bonded semiconductor at the desired length with a chamfer on the semiconductor cutback  
Stylus in option score the peelable semiconductor or chamfer the insulation

Silicone required for non peelable semiconductor



### Options

SRC-D - Scoring stylus for peelable semiconductor with chamfer on the transition  
SR - Scoring stylus for peelable semiconductor  
SCH - Chamfering stylus for insulation  
PCR2 - Quick set up right angled 45° handle

### Spare part

LASCR1 - Spare blade for bonded semiconductor  
PER - Quick set up right angled 90° handle

### Associated tool

TSA - Silicon tube  
DSP - Peelable semiconductor lifter  
GRI-RTE - Scraper for residues of bonded semiconductor screen with protective case

MV cables Tools  
**MF1+/60**



Part Number	Diameter	Tool capacity			Dimensions			Packaging
		Thickness capacity	Angle of the chamfer on the semiconductor	Remaining length of the semiconductor	Length	Width	Height	
<b>MF1+/25</b>	14 - 44 mm 0,551 - 1,732 in	0,4-1,4 mm / 0,016-0,055 in	14,5°	25-30-40-45 mm / 0,984- 1,181- 1,575- 1,772 in	190 mm 7,480 in	85 mm 3,346 in	125 mm 4,921 in	box
<b>MF1+/60</b>	18 - 60 mm 0,709 - 2,362 in	0,4-1,4 mm / 0,016-0,055 in	14,5°	30-40-45-50-55 mm / 1,181- 1,575- 1,772- 1,969- 2,165 in	305 mm 12,008 in	85 mm 3,346 in	100 mm 3,937 in	box