

Certifications

EN 60900:2012 - Approved by
ENEDIS

Section

LV Live working

Application

Field
Laboratory
Production

**PRODUCT BENEFITS**

Made of insulating material

Safety, light and easy to use

TOOL CAPACITY

Diameter	26 - 52 mm 1,024 - 2,047 inch
Circular cutting thickness capacity	2,0 mm / 0,079 in
Longitudinal cutting thickness capacity	2,0 mm / 0,079 in

TOOL DIMENSIONS

Length	265 mm
Width	97 mm
Height	73 mm
Weight without box	0,44 Kg
Packaging	Box

ALROC SAS

Z.I. de la Fonderie - 72160 TUFFE
FRANCE
Phone: +33 2 43 71 11 80
Fax number : +33 2 43 71 16 51
www.alroc.fr

Composite plier for LV cable**TO DO WHAT**

The PG3EC/2020 enables the user to make a circular and longitudinal cut in order to remove cable's outer sheath

PG3EC/2020 for cable Ø26 to 52 mm / 1,023 to 2,047 in (3x50² + 1x50² à 3x240 + 1x95²)

**Options**

SGM - Large size pouch

Spare part

MTC3E/20 - Spare blade for circular cutting 2,0 mm / 0,079 in (x4)

MTL3E/20 - Spare blade for longitudinal cutting 2,0 mm / 0,079 in

LV cables Tools

PG3EC/2020



Part Number	Diameter	Tool capacity		Dimensions			Packaging
		Circular cutting thickness capacity	Longitudinal cutting thickness capacity	Length	Width	Height	
PG3EC/2020	26 - 52 mm 1,024 - 2,047 in	2,0 mm / 0,079 in	2,0 mm / 0,079 in	265 mm 10,433 in	97 mm 3,819 in	73 mm 2,874 in	box